


FlexStor II - 2U



Automated backup solution for smaller data volumes



TECHNICAL SPECIFICATIONS

GENERAL	
Drive Type	Half-height, Full-height LTO 5, 6, 7, 8, 9
Interface Type	
Media Type	Ultrium 5, 6, 7, 8, 9 (Drive dependent)

FORM FACTOR	
19" rack mount	2 rack Unit high

CONFIGURATION	
Drive Capacity	1 full-height LTO or 2 half-height LTO
Slot Capacity	24
Mailslot Quantity	1
Numbers of Magazine	2

CAPACITY	
Native Capacity	432 TBytes (LTO-9)
Compressed Capacity (2,5:1)	1080 TBytes (LTO-9)

TECHNICAL SPECIFICATIONS

SPEED	
Transfer Rate	Drive and interface dependent

RELIABILITY	
Robotic MSBF	1,000,000

ACCESS AND OPERATION	
Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

POWER	
Power Supply Quantity	1
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	160W

ENVIRONMENTAL REQUIREMENTS	
Noise Emission	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)

PHYSICAL DIMENSIONS	
Width	447.5 mm (17.62 inches)
Depth	810 mm (31.9 inches)
Height	97,6 mm (3,84 inches)
Weight	22kg* (49lbs) *without tapes